

PVC COATED ALUMINUM LIQUIDTIGHT CONNECTORS - 90° W/GROUND

Description:

Calbond PVC coated aluminum liquidtight connectors are used with Aluminum Liquidtight Conduit. The sleeve on the aluminum liquidtight connector is sized specifically to tighten around PVC conduit. Pulling compound is recommended for ease of installation. Fittings are provided with a flexible sleeve on the conduit side and a sealing form on both the box side and the mating part of the gland.

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1/2" to 2"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2"
- For sizes 2-1/2" - 4", the length of the sleeve extension(s) shall be at least 2"
- Available in straight, 45 degree or 90 degree body configurations



Standards:

- UL Standard 514B
- CSA Standard: C22.2 No. 18

90° with Ground					
Aluminum Item Number	Trade Size	A	B	C	
PA0500LT5090GSA	1/2"	1.46	2.10	0.56	
PA0700LT7590GSA	3/4"	1.74	2.54	0.56	
PA1000LT10090GSA	1"	1.96	3.23	0.75	
PA1200LT12590GSA	1-1/4"	2.36	4.04	0.81	
PA1500LT15090GSA	1-1/2"	2.80	4.48	0.81	
PA2000LT20090GSA	2"	3.33	5.48	0.88	

