

PVC COATED LIQUIDTIGHT CONNECTORS - 90° W/GROUND

Description:

Calbond PVC coated liquidtight connectors are used with Liquidtight Conduit. The sleeve on the liquidtight connector is sized specifically to tighten around PVC conduit. Pulling compound is recommended for ease of installation. Fittings are provided with a flexible sleeve on the conduit side and a sealing form on both the box side and the mating part of the gland.

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Sizes available are 1/2" to 2"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2"
- For sizes 2-1/2" - 4", the length of the sleeve extension(s) shall be at least 2"
- Available in straight, 45 degree or 90 degree body configurations

Standards:

- UL Standard 514B
- CSA Standard: C22.2 No. 18



90° with Ground						
Item Number	Trade Size	A	B	C	Weight Per 100 (lbs)	
PV0300LT3890G	3/8"	1.24	1.80	0.56	30	
PV0500LT5090G	1/2"	1.46	2.10	0.56	30	
PV0700LT7590G	3/4"	1.74	2.54	0.56	40	
PV1000LT10090G	1"	1.96	3.23	0.75	60	
PV1200LT12590G	1-1/4"	2.36	4.04	0.81	100	
PV1500LT15090G	1-1/2"	2.80	4.48	0.81	170	
PV2000LT20090G	2"	3.33	5.48	0.88	270	
PV2500LT25090G	2-1/2"	3.83	10.92	1.00	380	
PV3000LT30090G	3"	4.58	12.3	1.00	420	
PV4000LT40090G	4"	5.58	14.7	1.13	620	

