

PVC COATED

SEALING FITTINGS - EZD FEMALE HUBS w/DRAIN & INSP. COVER

Description:

Calbond PVC Coated Sealing Fittings are used in hazardous locations to prevent flame and gas from continuing to travel through the conduit system. PVC coating provides corrosion protection. A sealing compound should be used on the interior after wiring. Compound supplied by the original fitting manufacturer.

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1/2" to 2"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2"
- Mating sealing forms are provided on all caps

Standards:

- National Electric Code/ CEC
EZD 111-611
Class I, Division 1 & 2, Groups C, D, Class III
- UL Standard 886
- CSA Standard: C22.2



Item Number	Trade Size	A	B	C	Turning Radius
<i>* For sealing in any position</i>					
PV0500EZD111	1/2"	4.19	3.08	3.46	2.06
PV0700EZD211	3/4"	4.19	3.08	3.71	2.19
PV1000EZD311	1"	4.94	3.58	3.96	2.44
PV1200EZD411	1-1/4"	4.94	3.58	4.39	2.63
PV1500EZD511	1-1/2"	5.19	3.58	4.64	2.69
PV2000EZD611	2"	7.13	5.64	5.33	3.69

