

PVC COATED SEALING FITTINGS - EZS MALE-FEMALE HUBS

Description:

Calbond PVC Coated Sealing Fittings are used in hazardous locations to prevent flame and gas from continuing to travel through the conduit system. PVC coating provides corrosion protection. A sealing compound should be used on the interior after wiring. Compound supplied by the original fitting manufacturer.

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1/2" to 3"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2"
- For sizes 2-1/2" - 3", the length of the sleeve extension(s) shall be at least 2".
- Mating sealing forms are provided on all caps
- Sealing sleeves on all conduit openings

Standards:

- National Electric Code/ CEC
EZS 16-86
Class I, Division 1 & 2, Groups C, D, Class III
- UL Standard 886
- CSA Standard: C22.2



Item Number	Trade Size	Weight Per 100 (lbs)	A	B	Turning Radius
<i>* For sealing in any position</i>					
PV0500EZS16	1/2"	200	4.19	2.58	1.88
PV0700EZS26	3/4"	240	4.19	2.58	1.88
PV1000EZS36	1"	300	4.94	3.08	2.13
PV1200EZS46	1-1/4"	400	5.06	3.08	2.31
PV1500EZS56	1-1/2"	460	5.19	3.33	3.34
PV2000EZS66	2"	690	7.06	5.27	3.28
PV2500EZS76	2-1/2"	920	7.94	5.27	3.38
PV3000EZS86	3"	870	8.63	5.96	3.88