

PVC COATED ALUMINUM CONDUIT HUBS - STG

Description:

Calbond PVC aluminum ST style hubs are used to terminate conduit runs through the wall of a sheet metal electrical enclosure. They are available with or without grounding lug. STTB style hubs are 'Through-Bulkhead' fittings used to pass conduit runs through firewalls or bulkheads up to 1/8" thick. STTTB style hubs perform the same function for unlimited wall thicknesses.

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- STG and STTB available in 12 trade sizes from 1/2" through 6"
- STTTB in sizes from 1/2" through 2"
- Sealing sleeves on conduit side of hub
- Molded PVC gasket seals flush with enclosure wall
- Neoprene O-ring gasket provides additional seal
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2"
- For sizes 2-1/2" - 6", the length of the sleeve extension(s) shall be at least 2"

Standards:

- UL 514B
- NEC/CEC:
 - Class I, Division 2,
 - Class II, Division 1 & 2
 - Class III, Division 1 & 2
 - Class I, Zone 1, AEx e II
 - Class I, Zone 1, Ex e II
- All Screw-tight Hubs are listed for NEMA type enclosures 2, 3, 3R, 4, 4x, 11 and 12
- Grounding and Bonding Hubs are listed for NEMA Enclosures 2, 3, 3R, 4 and 12



STG						
Aluminum Item Number	Trade Size	A	B	C	Max Wall Thickness	
PA0500STAG1	1/2"	1.84	2.00	1.31	0.125	
PA0700STAG2	3/4"	2.22	2.25	1.66	0.125	
PA1000STAG3	1"	2.66	2.50	2.03	0.125	
PA1200STAG4	1-1/4"	2.94	3.25	2.28	0.125	
PA1500STAG5	1-1/2"	3.19	3.50	2.53	0.125	
PA2000STAG6	2"	3.75	4.25	3.09	0.125	
PA2500STAG7	2-1/2"	4.22	4.75	3.28	0.125	
PA3000STAG8	3"	4.31	5.25	3.38	0.125	
PA3500STAG9	3-1/2"	4.38	5.50	3.44	0.125	
PA4000STAG10	4"	4.44	6.25	3.50	0.125	
PA5000STAG11	5"	4.94	7.50	4.00	0.125	
PA6000STAG12	6"	5.00	8.50	4.00	0.125	

