

PVC COATED ALUMINUM MALLEABLE FITTINGS - 90° FEMALE-FEMALE

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- Sizes available are 1/2" to 2 1/2"

Applications:

Calbond PVC EL Style Aluminum Elbows are used where a very tight radius elbow is required. They are available with female & male threaded connections. Female threaded hubs are supplied with a sealing sleeve. Male ends are supplied with a sealing form.



Standards:

- NEC/CEC EL 19-39 Class I, Division 1 & 2, Groups A, B, C, D Class III, EL 49-79 Class I, Division 1 & 2, Groups C, D Class III
- UL Standard: 886
- CSA Standard: C22.2 No. 30

| Part Number | Trade Size (in) | A (in) |
|--------------|-----------------|--------|
| PA0500EL19SA | 1/2 | 2.03 |
| PA0700EL29SA | 3/4 | 2.50 |
| PA1000EL39SA | 1 | 3.00 |
| PA1200EL49SA | 1 1/4 | 3.50 |
| PA1500EL59SA | 1 1/2 | 5.50 |
| PA2000EL69SA | 2 | 7.00 |
| PA2500EL79SA | 2 1/2 | 8.44 |

