

PVC COATED ALUMINUM MOGUL FITTINGS - BC

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1" to 4"
- Sealing sleeves on all hubs

Applications:

Calbond PVC Coated Aluminum Mogul Style Conduit Bodies are used where an extra larger wiring space is required. They are available in all styles. Sealing mating between cover and fittings are provided.

Standards:

- UL Standard 514B
- CSA Standard: C22.2 No. 18



BC ALUMINUM							
Part Number	Trade Size (in)	A (in)	B (in)	C (in)	D (in)	E (in)	Weight per 100 (lbs)
PA1000BC3SA	1	7.31	1.92	2.27	1.88	6	3.2
PA1200BC4SA	1¼	8.50	2.35	2.27	1.88	6	4.0
PA1500BC5SA	1½	10.38	2.60	3.08	2.63	10	5.9
PA2000BC6SA	2	12.25	3.17	3.08	2.63	10	7.8
PA2500BC7SA	2½	15.63	3.67	4.33	3.81	15	12.5
PA3000BC8SA	3	15.63	4.42	4.33	3.81	15	17.0
PA3500BC9SA	3½	18.75	4.92	5.33	4.75	20	25.0
PA4000BC10SA	4	18.75	5.42	5.33	4.75	20	28.0

