

PVC COATED ALUMINUM MOGUL FITTINGS - BT

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1" to 4"
- Sealing sleeves on all hubs

Applications:

Calbond PVC Coated Aluminum Mogul Style Conduit Bodies are used where an extra larger wiring space is required. They are available in all styles. Sealing mating between cover and fittings are provided

Standards:

- UL Standard: 514B
- CSA Standard: C22.2 No. 18



BT ALUMINUM							
Part Number	Trade Size (in)	A (in)	B (in)	C (in)	D (in)	E (in)	Weight per 100 (lbs)
PA1000BT3SA	1	11.56	1.92	4.20	1.88	6	3.2
PA1200BT4SA	1¼	12.06	2.35	4.45	1.88	6	3.6
PA1500BT5SA	1½	16.75	2.60	5.60	2.63	10	7.5
PA2000BT6SA	2	17.75	3.17	6.10	2.63	10	9.0
PA2500BT7SA	2½	22.38	3.67	7.63	3.81	15	15.0
PA3000BT8SA	3	22.38	4.42	7.76	3.81	15	19.0
PA3500BT9SA	3½	27.75	4.92	8.92	4.75	20	29.0
PA4000BT10SA	4	27.75	5.42	8.92	4.75	20	32.0

