

PVC COATED ALUMINUM SEALING FITTINGS EYD MALE FEMALE HUBS W/DRAIN

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are ½" to 4"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes ½" - 2". For sizes 2 ½" - 4", the length of the sleeve extension(s) shall be at least 2".
- Sealing sleeve is provided on plug hub (patching compound recommended on top of plug)
- Mating sealing forms are provided on all caps
- Sealing sleeves on all conduit openings


Applications:

Calbond PVC Aluminum Coated Sealing Fittings are used in hazardous locations to prevent flame and gas from continuing to travel through the conduit system. PVC coating provides corrosion protection. A sealing compound should be used on the interior after wiring. Compound supplied by the original fitting manufacturer.



Standards:

- NEC/CEC:
 - EYD-11-101, 116-1016
Class I, Division 1 & 2,
Groups B, C, D Class III
 - EYD1-10, 16-106
Class I, Division 1 & 2,
Groups C, D Class III
 - EZD10-60, 111-611
Class I, Division 1 & 2,
Groups C, D Class III
- UL Standard: 1203
- CSA Standard: C22.2



Aluminum Part Number	Trade Size (in)	A (in)	B (in)	Turning Radius
<i>For Sealing in Vertical or Horizontal Positions</i>				
PA0500EYD16SA	½	3.28	1.33	1.63
PA0700EYD26SA	¾	3.69	1.58	1.91
PA1000EYD36SA	1	4.31	2.27	2.38
PA1200EYD46SA	1¼	5.06	2.27	1.84
PA1500EYD56SA	1½	5.5	2.52	2.06
PA2000EYD66SA	2	6.25	3.08	2.31
PA2500EYD76SA	2½	7.5	3.58	2.69
PA3000EYD86SA	3	8.5	4.33	3.31
PA3500EYD96SA	3½	9.19	4.83	3.44
PA4000EYD106SA	4	9.75	5.33	3.5

