

# PVC COATED ALUMINUM CONDUIT HUBS - STG


## Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- STG available in 12 trade sizes from ½" through 6"
- Molded PVC gasket seals flush with enclosure wall
- Neoprene O-ring gasket provides additional seal
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2"
- For sizes 2½" - 6", the length of the sleeve extension(s) shall be at least 2"



## Applications:

Allied Tube & Conduit® PVC STG Style Hubs are used to terminate conduit runs into electrical enclosures. Conduit hubs are available with or without grounding lug. PVC coating and internal urethane coating provide for superior corrosion protection. Electrical continuity is maintained across assembled joints.



## Standards:

- NEC/CEC:
  - Class I, Division 2,
  - Class II, Division 1 & 2
  - Class III, Division 1 & 2
  - Class I, Zone 1, AEx e II
  - Class I, Zone 1, Ex e II
- All Screw-tight Hubs are manufactured in accordance with NEMA type enclosures 2, 3, 3R, 4, 4x, 11 and 12
- Grounding and Bonding Hubs are manufactured in accordance with NEMA Enclosures 2, 3, 3R, 4 and 12

Part Number	Trade Size (in)	A (in)	B (in)	C (in)	Max Wall Thickness (in)
PA0500STAG1	½	1.84	2.00	1.31	0.125
PA0700STAG2	¾	2.22	2.25	1.66	0.125
PA1000STAG3	1	2.66	2.50	2.03	0.125
PA1200STAG4	1¼	2.94	3.25	2.28	0.125
PA1500STAG5	1½	3.19	3.50	2.53	0.125
PA2000STAG6	2	3.75	4.25	3.09	0.125
PA2500STAG7	2½	4.22	4.75	3.28	0.125
PA3000STAG8	3	4.31	5.25	3.38	0.125
PA3500STAG9	3½	4.38	5.50	3.44	0.125
PA4000STAG10	4	4.44	6.25	3.50	0.125
PA5000STAG11	5	4.94	7.50	4.00	0.125
PA6000STAG12	6	5.00	8.50	4.00	0.125

