

# PVC COATED ALUMINUM MOGUL FITTINGS - BUB

## Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1" to 4"
- Sealing sleeves on all hubs

## Applications:

Calbond PVC Coated Aluminum Mogul Style Conduit Bodies are used where an extra larger wiring space is required. They are available in all styles. Sealing mating between cover and fittings are provided.

## Standards:

- UL Standard 514B
- CSA Standard: C22.2 No. 18



Part Number	Trade Size (in)	A (in)	B (in)	C (in)	D (in)	E (in)	Weight per 100 (lbs)
PA1000BUB3SA	1	10.19	2.73	2.27	1.88	6	3.2
PA1200BUB4SA	1 1/4	11.06	3.23	2.27	1.88	6	4.0
PA1500BUB5SA	1 1/2	15.00	3.54	3.08	2.63	10	5.9
PA2000BUB6SA	2	15.50	4.17	3.08	2.63	10	7.8
PA2500BUB7SA	2 1/2	19.75	4.85	4.33	3.81	15	12.5
PA3000BUB8SA	3	19.88	6.57	4.33	3.81	15	17.0
PA3500BUB9SA	3 1/2	25.38	6.42	5.33	4.75	20	25.0
PA4000BUB10SA	4	25.25	6.85	5.33	4.75	20	28.0

