

PVC COATED ALUMINUM LBD PULLING STYLE ELBOWS

Features:


- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are ½" to 4"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2"- 2"
- For sizes 2½- 4", the length of the sleeve extension(s) shall be at least 2"
- PVC seal between fitting and cover

Applications:

Calbond LBD Aluminum Style Fittings provides for easy wire pulling in tight radius bends. Allied Tube & Conduit® LBD fittings provide for a seal in the PVC coating between the fitting and the cover.

Standards:

- UL 514 B
- CSA C22.2 No. 18



Aluminum Part Number	Trade Size (in)	Weight per 100 (lbs)
PA0500LBD1100SA	½	120
PA0700LBD2200SA	¾	200
PA1000LBD3300SA	1	250
PA1200LBD4400SA	1 ¼	600
PA1500LBD5500SA	1 ½	1150
PA2000LBD6600SA	2	1800
PA2500LBD7700SA	2 ½	2200
PA3000LBD8800SA	3	3500
PA3500LBD9900SA	3 ½	6000
PA4000LBD10900SA	4	7000

