

# PVC COATED SEALING FITTINGS EYD FEMALE HUBS W/DRAIN

## Features:


- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1/2" to 4"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2". For sizes 2 1/2" - 4", the length of the sleeve extension(s) shall be at least 2".
- Sealing sleeve is provided on plug hub (patching compound recommended on top of plug)
- Mating sealing forms are provided on all caps
- Sealing sleeves on all conduit openings

## Applications:

Calbond PVC Coated Sealing Fittings are used in hazardous locations to prevent flame and gas from continuing to travel through the conduit system. PVC coating provides corrosion protection. A sealing compound should be used on the interior after wiring. Compound supplied by the original fitting manufacturer.

## Standards:

- NEC/CEC:
  - EYD-11-101, 116-1016  
Class I, Division 1 & 2,  
Groups B, C, D Class III
  - EYD1-10, 16-106  
Class I, Division 1 & 2,  
Groups C, D Class III
  - EZD10-60, 111-611  
Class I, Division 1 & 2,  
Groups C, D Class III
- UL Standard: 886
- CSA Standard: C22.2



Aluminum Part Number	Trade Size (in)	Weight per 100 (lbs)	A (in)	B (in)	Turning Radius
PV0500EYD1	1/2	140	3.28	1.33	1.63
PV0700EYD2	3/4	170	3.69	1.58	1.91
PV1000EYD3	1	230	4.31	2.27	2.38
PV1200EYD4	1 1/4	250	5.06	2.27	1.84
PV1500EYD5	1 1/2	400	5.5	2.52	2.06
PV2000EYD6	2	470	6.25	3.08	2.31
PV2500EYD7	2 1/2	900	7.5	3.58	2.69
PV3000EYD8	3	1020	8.5	4.33	3.31
PV3500EYD9	3 1/2	1050	9.19	4.83	3.44
PV4000EYD10	4	400	9.75	5.33	3.5



# PVC COATED SEALING FITTINGS EYD FEMALE HUBS W/DRAIN

Aluminum Part Number	Trade Size (in)	Weight per 100 (lbs)	A (in)	B (in)	Turning Radius
PV0500EYD11	½	140	3.28	1.33	1.63
PV0700EYD21	¾	170	3.69	1.58	1.91
PV1000EYD31	1	230	4.31	2.27	2.38
PV1200EYD41	1 ¼	250	5.06	2.27	1.84
PV1500EYD51	1 ½	400	5.5	2.52	2.06
PV2000EYD61	2	470	6.25	3.08	2.31
PV2500EYD71	2 ½	900	7.5	3.58	2.69
PV3000EYD81	3	1020	8.5	4.33	3.31
PV3500EYD91	3 ½	1050	9.19	4.83	3.44
PV4000EYD101	4	400	9.75	5.33	3.5

