

PVC COATED SEALING FITTINGS EYD MALE FEMALE HUBS W/DRAIN

Features:


- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1/2" to 4"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2". For sizes 2 1/2" - 4", the length of the sleeve extension(s) shall be at least 2".
- Sealing sleeve is provided on plug hub (patching compound recommended on top of plug)
- Mating sealing forms are provided on all caps
- Sealing sleeves on all conduit openings

Applications:

Calbond PVC Coated Sealing Fittings are used in hazardous locations to prevent flame and gas from continuing to travel through the conduit system. PVC coating provides corrosion protection. A sealing compound should be used on the interior after wiring. Compound supplied by the original fitting manufacturer.

Standards:

- NEC/CEC:
 - EYD-11-101, 116-1016
Class I, Division 1 & 2,
Groups B, C, D Class III
 - EYD1-10, 16-106
Class I, Division 1 & 2,
Groups C, D Class III
 - EZD10-60, 111-611
Class I, Division 1 & 2,
Groups C, D Class III
- UL Standard: 886
- CSA Standard: C22.2



Aluminum Part Number	Trade Size (in)	Weight per 100 (lbs)	A (in)	B (in)	Turning Radius
<i>For Sealing in Vertical or Horizontal Positions</i>					
PV0500EYD16	1/2	270	3.28	1.33	1.63
PV0700EYD26	3/4	280	3.69	1.58	1.91
PV1000EYD36	1	290	4.31	2.27	2.38
PV1200EYD46	1 1/4	260	5.06	2.27	1.84
PV1500EYD56	1 1/2	370	5.50	2.52	2.06
PV2000EYD66	2	520	6.25	3.08	2.31
PV2500EYD76	2 1/2	950	7.50	3.58	2.69
PV3000EYD86	3	1130	8.5	4.33	3.31
PV3500EYD96	3 1/2	1250	9.19	4.83	3.44
PV4000EYD106	4	1670	9.75	5.33	3.5



PVC COATED SEALING FITTINGS EYD MALE FEMALE HUBS W/DRAIN

Aluminum Part Number	Trade Size (in)	Weight per 100 (lbs)	A (in)	B (in)	Turning Radius
<i>For Sealing in Vertical or Horizontal Positions</i>					
PV0500EYD116	½	270	3.28	1.33	1.63
PV0700EYD216	¾	280	3.69	1.58	1.91
PV1000EYD316	1	290	4.31	2.27	2.38
PV1200EYD416	1¼	260	5.06	2.27	1.84
PV1500EYD516	1½	370	5.5	2.52	2.06
PV2000EYD616	2	520	6.25	3.08	2.31
PV2500EYD716	2½	950	7.5	3.58	2.69
PV3000EYD816	3	1130	8.5	4.33	3.31
PV3500EYD916	3½	1250	9.19	4.83	3.44
PV4000EYD1016	4	1670	9.75	5.33	3.5

