

PVC COATED SEALING FITTINGS EZS MALE-FEMALE HUBS

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1/2" to 3"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2"
- For sizes 2 1/2" - 3", the length of the sleeve extension(s) shall be at least 2"
- Mating sealing forms are provided on all caps
- Sealing sleeves on all conduit openings

Applications:

Calbond PVC Coated Sealing Fittings are used in hazardous locations to prevent flame and gas from continuing to travel through the conduit system. PVC coating provides corrosion protection. A sealing compound should be used on the interior after wiring. Compound supplied by the original fitting manufacturer.

Standards:

- NEC/CEC:
EZS 16-86
Class I, Division 1 & 2,
Groups C, D Class III
- UL Standard: 1203
- CSA Standard: C22.2



Item Number	Trade Size (in)	Weight per 100 (lbs)	A (in)	B (in)	Turning Radius (in)
For Sealing in Any Position					
PV0500EZS16	1/2	200	4.19	2.58	1.88
PV0700EZS26	3/4	240	4.19	2.58	1.88
PV1000EZS36	1	300	4.94	3.08	2.13
PV1200EZS46	1 1/4	400	5.06	3.08	2.31
PV1500EZS56	1 1/2	460	5.19	3.33	3.34
PV2000EZS66	2	690	7.06	5.27	3.28
PV2500EZS76	2 1/2	920	7.94	5.27	3.38
PV3000EZS86	3	870	8.63	5.96	3.88

