

# PVC COATED EXPANSION/ DEFLECTION COUPLING XD

## Features:

- Axial expansion or contraction up to 3/4"
- Angular misalignment in any direction to 30°
- 40 mil carbon gray PVC exterior coating
- 2 mil light gray urethane interior coating
- XD in 10 trade sizes from 1" through 5"
- Sealing sleeves



## Applications:

Calbond XD Expansion/Deflection Couplings are used with PVC coated rigid conduit to accommodate axial expansion, angular misalignment and parallel misalignment. They feature an internal bonding jumper. PVC coating and internal urethane coating provide for superior corrosion protection. Electrical continuity is maintained across assembled joints.

Galvanized Part Number	Trade Size (in)	A (in)	B (in)
PV1000XD3	1	7.00	3.94
PV1200XD4	1¼	7.375	4.25
PV1500XD5	1½	7.25	4.5
PV2000XD6	2	7.25	4.94
PV2500XD7	2½	7.5	5.3125
PV3000XD8	3	7.625	5.94
PV3500XD9	3½	7.75	6.5
PV4000XD10	4	7.875	6.94
PV5000XD12	5	7.75	8

All dimensions are for informational purposes only \*Tolerances +/- 5%



For more info visit [calbond.com](http://calbond.com) 