

PVC COATED DEVICE BOXES - FDC

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- Sizes available are ½" to 1"
- Sealing sleeves on all conduit openings
- Modified boxes are available upon request
- All available covers are supplied with PVC coating

Applications:

Calbond Type FS & FD PVC Coated Device Boxes and Covers offer corrosion protection to conduit systems and accommodates wiring devices and access for taps and splices. Covers are available separately. Electrical continuity of the conduit system is maintained across assembled system.



Standards:

- UL Listed Standard 514B, File # 307133
- CSA Standard: C22.2 No. 18

| Part Number | Trade Size (in) | Weight per 100 (lbs) | A (in) | B (in) | C (in) | D (in) | Aluminum Item Number |
|-------------|-----------------|----------------------|--------|--------|--------|--------|----------------------|
| PV0500FDC1 | ½ | 270 | 1.380 | 1.920 | 2.690 | 0.670 | PA0500FDC1SA |
| PV0700FDC2 | ¾ | 280 | 1.630 | 1.920 | 2.690 | 0.790 | PA0700FDC2SA |
| PV1000FDC3 | 1 | 310 | 2.000 | 1.920 | 2.690 | 0.920 | PA1000FDC3SA |

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit calbond.com