

# PVC COATED DEVICE BOXES - FS

## Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- Sizes available are ½" to 1"
- Sealing sleeves on all conduit openings
- Modified boxes are available upon request
- All available covers are supplied with PVC coating

## Applications:

Calbond Type FS PVC Coated Device Boxes offer corrosion protection to conduit systems and accommodates wiring devices and access for taps and splices. Covers are available separately. Electrical continuity of the conduit system is maintained across assembled system.



## Standards:

- UL Listed Standard 514B File #E307133
- CSA Standard: C22.2 No. 18

Part Number	Trade Size (in)	Weight per 100 (lbs)	A (in)	B (in)	C (in)	D (in)	Aluminum Item Number
<b>Single Gang</b>							
PV0500FS1	½	3.20	1.380	1.920	1.690	0.670	PA0500FS1SA
PV0700FS2	¾	3.30	1.630	1.920	1.690	0.790	PA0700FS2SA
PV1000FS3	1	3.50	2.000	1.920	1.690	0.920	
<b>Double Gang</b>							
PV0500FS12	½	3.30	1.380	1.920	1.690	0.670	PA0500FS12SA
PV0700FS22	¾	3.40	1.630	1.920	1.690	0.790	PA0700FS22SA
PV1000FS32	1	3.60	2.000	1.920	1.690	0.920	

All dimensions are for informational purposes only \*Tolerances +/- 5%



For more info visit [calbond.com](http://calbond.com)

