

# PVC COATED DEVICE BOXES - FSC

## Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- Sizes available are ½" to 1"
- Sealing sleeves on all conduit openings
- Modified boxes are available upon request
- All available covers are supplied with PVC coating

## Applications:

Calbond Type FSC PVC Coated Device Boxes offer corrosion protection to conduit systems and accommodates wiring devices and access for taps and splices. Covers are available separately. Electrical continuity of the conduit system is maintained across assembled system.



## Standards:

- UL Listed Standard 514B File #E307133
- CSA Standard: C22.2 No. 18

Part Number	Trade Size (in)	Weight per 100 (lbs)	A (in)	B (in)	C (in)	D (in)	Aluminum Item Number
<b>Single Gang</b>							
PV0500FSC1	½	2.20	1.380	1.920	1.690	0.670	PA0500FSC1SA
PV0700FSC2	¾	2.40	1.630	1.920	1.690	0.790	PA0700FSC2SA
PV1000FSC3	1	2.70	2.000	1.920	1.690	0.920	
<b>Double Gang</b>							
PV0500FSC12	½	3.30	1.380	1.920	1.690	0.670	
PV0700FSC222	¾	3.60	1.630	1.920	1.690	0.790	
PV1000FSC32	1	4.00	2.000	1.920	1.690	0.920	

All dimensions are for informational purposes only \*Tolerances +/- 5%



For more info visit [calbond.com](http://calbond.com)

