

# PVC COATED GUA JUNCTION BOXES FOR HAZARDOUS LOCATIONS - GUAD

## Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are ½" to 1¼"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes ½" - 1¼"

## Applications:

Calbond GUA Style Fittings are available in a variety of shapes and dimensions. GUA style boxes are used in hazardous locations. All GUA style boxes are supplied PVC coated with PVC coated covers and a seal between the coating of the boxes and the coating of the covers.



## Standards:

- National Electric Code:  
Class I, Division 1 & 2, Groups C, D, Class III
- UL Standard 886
- ANSI Standard C-33.27
- CSA Standard: C22.2 No. 30
- NEMA/EEMAC 3, 4

Part Number	Trade Size (in)	Cover Opening (in)	A (in)	B (in)	C (in)	D (in)	Weight per 100 (lbs)
PV0500GUAD14	½	2	2.58	1.85	1.75	0.67	200
PV0500GUAD16	½	3	3.58	2.04	1.88	0.79	320
PV0700GUAD24	¾	2	2.58	2.04	2.00	0.79	350
PV0700GUAD26	¾	3	2.58	2.04	1.88	0.79	380
PV1000GUAD36	1	3	3.58	2.35	2.19	0.92	380
PV1200GUAD47	1 1/4	5	5.83	3.85	3.75	1.13	1090

All dimensions are for informational purposes only \*Tolerances +/- 5%



For more info visit [calbond.com](http://calbond.com)