


PVC COATED CONDUIT HUBS - STG

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- STG available in 12 trade sizes from ½" through 6"
- STTTB in sizes available are ½" to 2"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2"- 2"
- For sizes 2½"- 6", the length of the sleeve extension(s) shall be at least 2"

Applications:

Allied Tube & Conduit® PVC STG Style Hubs are used to terminate conduit runs into electrical enclosures. Conduit hubs are available with or without grounding lug. PVC coating and internal urethane coating provide for superior corrosion protection. Electrical continuity is maintained across assembled joints.



Standards:

- UL Listed File#E352416
- NEC/CEC:
 - Class I, Division 2,
 - Class II, Division 1 & 2
 - Class III, Division 1 & 2
 - Class I, Zone 1, AEx e II
 - Class I, Zone 1, Ex e II
- All Screw-tight Hubs are manufactured in accordance with NEMA type enclosures 2, 3, 3R, 4, 4x, 11 and 12
- Grounding and Bonding Hubs are manufactured in accordance with NEMA Enclosures 2, 3, 3R, 4 and 12

Part Number	Trade Size (in)	A (in)	B (in)	C (in)	Max Wall Thickness (in)	Weight Per 100 (lbs)
PV0500STG1	½	1.84	2.00	1.31	0.125	20
PV0700STG2	¾	2.22	2.25	1.66	0.125	30
PV1000STG3	1	2.66	2.50	2.03	0.125	40
PV1200STG4	1¼	2.94	3.25	2.28	0.125	40
PV1500STG5	1½	3.19	3.50	2.53	0.125	60
PV2000STG6	2	3.75	4.25	3.09	0.125	120
PV2500STG7	2½	4.22	4.75	3.28	0.125	150
PV3000STG8	3	4.31	5.25	3.38	0.125	210
PV3500STG9	3½	4.38	5.50	3.44	0.125	300
PV4000STG10	4	4.44	6.25	3.50	0.125	350
PV5000STG11	5	4.94	7.50	4.00	0.125	540
PV6000STG12	6	5.00	8.50	4.00	0.125	690

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit calbond.com