

# PVC COATED MOGUL FITTINGS - BLB

## Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1" to 4"
- Sealing sleeves on all hubs

## Applications:

Calbond PVC Coated Mogul Style Conduit Bodies are used where an extra larger wiring space is required. They are available in all styles. Sealing mating between cover and fittings are provided.

## Standards:

- UL Standard: 514B
- CSA Standard: C22.2 No. 18



BLB							
Part Number	Trade Size (in)	A (in)	B (in)	C (in)	D (in)	E (in)	Weight per 100 (lbs)
PV1000BLB3	1	9.63	2.88	2.27	1.88	6	3.2
PV1200BLB4	1¼	9.88	3.32	2.27	1.88	6	4.2
PV1500BLB5	1½	14.23	3.67	3.08	2.63	10	6.0
PV2000BLB6	2	14.73	4.23	3.08	2.63	10	7.0
PV2500BLB7	2½	18.95	5.13	4.33	3.81	15	13.8
PV3000BLB8	3	18.95	5.88	4.33	3.81	15	17.5
PV3500BLB9	3½	24.17	6.54	5.33	4.75	20	25.0
PV4000BLB10	4	24.17	7.04	5.33	4.75	20	28.0

