

PVC COATED MOGUL FITTINGS - BT

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1" to 4"
- Sealing sleeves on all hubs

Applications:

Calbond PVC Coated Mogul Style Conduit Bodies are used where an extra larger wiring space is required. They are available in all styles. Sealing mating between cover and fittings are provided

Standards:

- UL Standard: 514B
- CSA Standard: C22.2 No. 18



BT							
Part Number	Trade Size (in)	A (in)	B (in)	C (in)	D (in)	E (in)	Weight per 100 (lbs)
PV1000BT3	1	11.56	1.92	4.20	1.88	6	3.2
PV1200BT4	1¼	12.06	2.35	4.45	1.88	6	3.6
PV1500BT5	1½	16.75	2.60	5.60	2.63	10	7.5
PV2000BT6	2	17.75	3.17	6.10	2.63	10	9.0
PV2500BT7	2½	22.38	3.67	7.63	3.81	15	15.0
PV3000BT8	3	22.38	4.42	7.76	3.81	15	19.0
PV3500BT9	3½	27.75	4.92	8.92	4.75	20	29.0
PV4000BT10	4	27.75	5.42	8.92	4.75	20	32.0

