


PVC COATED RIGID STEEL CONDUIT

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- Specialized corrosion resistant coating provided on threads
- Sizes available are ½" to 6"
- Color coded thread protectors
- Couplings shipped with conduit are packaged separately
- Hot Dipped Galvanized (HDG) conduit



Applications:

Calbond PVC Coated Rigid Steel Conduit is used for highly corrosive environments. The coating will provide corrosion protection and mechanical protection. Ground continuity is maintained throughout the installation.

Standards:

Allied Tube & Conduit® is UL listed with both the PVC coating as a primary protection and the Hot Dipped Galvanized (HDG) zinc coating as the primary protection per UL6. PVC coated conduit is restricted for use with threaded fittings only (threadless connector not permitted).

- UL/cUL listed in accordance to UL6 & ANSI C80.1 Standards
- UL/cUL listed rigid ferrous metal conduit with polyvinyl chloride coating verified for PVC adhesion performance
- Complies with NEMA RN-1
- UL File Number E226472

Galvanized Part Number	Trade Size (in)	Metric Size (mm)	Wall Thickness (in)	Outside Diam. w/ Coating (in)	Inside Diam. (in)	Weight / 100 (lbs)	Feet / Bundle
PV0510CT00	½	16	0.104	0.920	0.632	90	1000
PV0710CT00	¾	21	0.107	1.130	0.836	119	900
PV1010CT00	1	27	0.126	1.395	1.063	175	750
PV1210CT00	1¼	35	0.133	1.740	1.394	237	420
PV1510CT00	1½	41	0.138	1.980	1.642	281	380
PV2010CT00	2	53	0.146	2.455	2.083	376	300
PV2510CT00	2½	63	0.193	2.955	2.489	593	170
PV3010CT00	3	78	0.205	3.580	3.090	772	140
PV3510CT00	3½	91	0.215	4.080	3.570	922	110
PV4010CT00	4	103	0.225	4.580	4.050	1089	110
PV5010CT00	5	129	0.245	5.643	5.073	1488	80
PV6010CT00	6	155	0.266	6.705	6.093	1998	50

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit calbond.com 