

PVC COATED REDUCING COUPLINGS

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- Sizes available are 3/4" to 5"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2"- 2".
- For sizes 2½" - 5", the length of the sleeve extension(s) shall be at least 2".

Applications:

Calbond Reducing Couplings are used to join conduit and fittings of different sizes. They are provided with different size sleeves to match the fittings thread sizes.

Standards:

- National Electric Code/ CEC
 - REC 21 - 01210
 - Class I, Division 1 & 2, Groups A, B, C, D
 - Class III
- UL Standard: 886
- CSA Standard: C22.2 No. 30



| Part Number | Trade Size (in) | Weight per 100 (LBS) |
|----------------|-----------------|----------------------|
| PV0700REC21 | ¾ - ½ | 20 |
| PV1000REC31 | 1 - ½ | 70 |
| PV1000REC32 | 1 - ¾ | 50 |
| PV1200REC42 | 1¼ - ¾ | 100 |
| PV1200REC43 | 1¼ - 1 | 80 |
| PV1500REC52 | 1½ - ¾ | 140 |
| PV1500REC53 | 1½ - 1 | 120 |
| PV1500REC54 | 1½ - 1¼ | 130 |
| PV2000REC602 | 2 - ¾ | 150 |
| PV2000REC603 | 2 - 1 | 230 |
| PV2000REC604 | 2 - 1¼ | 260 |
| PV2000REC605 | 2 - 1½ | 280 |
| PV2500REC75 | 2½ - 1½ | 320 |
| PV3000REC86 | 3 - 2 | 370 |
| PV3500REC97 | 3½ - 2½ | 460 |
| PV4000REC108 | 4 - 3 | 590 |
| PV5000REC01210 | 5 - 4 | 740 |

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit calbond.com