

PVC COATED CONDUIT HUBS - STTB

Features:


- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- STTB available in 10 trade sizes from ½" through 4"
- Sealing sleeves on conduit side of hub
- Molded PVC gasket seals flush with enclosure wall
- Neoprene O-ring gasket provides additional seal
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes ½"- 2"
- For sizes 2½" - 4", the length of the sleeve extension(s) shall be at least 2"

Applications:

Calbond PVC STTB style hubs are used to terminate conduit runs through the wall of a sheet metal electrical enclosure. They are available with or without grounding lug. STTB style hubs are 'Through-Bulkhead' fittings used to pass conduit runs through firewalls or bulkheads up to ⅛" thick.

Standards:

- UL 514B
- NEC/CEC:
 - Class I, Division 2,
 - Class II, Division 1 & 2
 - Class III, Division 1 & 2
 - Class I, Zone 1, AEx e II
 - Class I, Zone 1, Ex e II
- All Screw-tight Hubs are manufactured in accordance with NEMA type enclosures 2, 3, 3R, 4, 4x, 11 and 12



Part Number	Trade Size (in)	A (in)	B (in)	C (in)	Max Wall Thickness (in)
PV0500STTB1	½	1.84	2.00	1.31	0.190
PV0700STTB2	¾	2.22	2.25	1.66	0.190
PV1000STTB3	1	2.66	2.50	2.03	0.250
PV1200STTB4	1¼	2.94	3.25	2.28	0.250
PV1500STTB5	1½	3.19	3.50	2.53	0.250
PV2000STTB6	2	3.75	4.25	3.09	0.250
PV2500STTB7	2½	4.22	4.75	3.28	0.250
PV3000STTB8	3	4.31	5.25	3.38	0.250
PV3500STTB9	3½	4.38	5.50	3.44	0.250
PV4000STTB10	4	4.44	6.25	3.50	0.250

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit calbond.com 