

PVC COATED SPLIT COUPLINGS

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- Sizes available are ½" to 6"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes ½"- 2"
- For sizes 2½" - 2½" to 3", the length of the sleeve extension(s) shall be at least 2"
- Stainless steel hardware included

Applications:

Calbond PVC Coated Split Couplings are used to connect two pieces of conduit where the conduit cannot be turned. Calbond split couplings are PVC coated for corrosion protection.



Standards:

- UL Standard 514B
- CSA Standard: C22.2 No. 18

Part Number	Trade Size (in)	Metric Size (mm)
PV0500TCC1	½	20
PV0700TCC2	¾	30
PV1000TCC3	1	40
PV1200TCC4	1¼	60
PV1500TCC5	1½	70
PV2000TCC6	2	100
PV2500TCC7	2½	230
PV3000TCC8	3	300
PV3500TCC9	3½	380
PV4000TCC10	4	410
PV5000TCC12	5	600
PV6000TCC14	6	860

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit calbond.com

