

PVC COATED TECK CONNECTORS

Features:

- Manufactured in aluminum for increased corrosion resistance
- One piece compact design
- Unique Grounding Seal for superior connectivity
- No Disassembly required for easy & fast installations
- Neoprene bushing provides pull out and sealing protection

Applications:

Calbond PVC Coated Aluminum TECK Connectors are designed to form a watertight seal around the jacketed metal cable and at the enclosure entry. Rated NEMA 4 and IP 65, these connectors are in-stock in ½" to 4" hub sizes.

Standards:

- NEMA 4, IP65

Material:

- Body - Aluminum



Part Number	Trade Size (in)	Exposed Armor Length (in)	Cable Range Over Jacket		Cable Range Over Armor		Dimension A (in)	Dimension B (in)
			Min (in)	Max (in)	Min (in)	Max (in)		
PA0500RTK-1	1/2	7/8	0.525	0.650	0.415	0.570	2.10	1.53
PA0500RTK-2	1/2	7/8	0.650	0.776	0.540	0.695	2.10	1.53
PA0500RTK-3	1/2	7/8	0.750	0.875	0.640	0.795	2.10	1.53
PA0500RTK-4	1/2	7/8	0.860	0.985	0.750	0.905	2.10	1.53
PA0700RTK-5	3/4	1	0.955	1.080	0.845	1.000	2.45	2.20
PA0700RTK-6	3/4	1	1.080	1.205	0.970	1.125	2.45	2.20
PA1000RTK-7	1	1	1.205	1.350	1.095	1.270	2.45	2.47
PA1200RTK-8	1 1/4	1 1/4	1.350	1.475	1.240	1.395	3.35	2.97
PA1200RTK-9	1 1/4	1 1/4	1.475	1.600	1.365	1.520	3.35	2.97
PA1200RTK-10	1 1/4	1 1/4	1.600	1.725	1.490	1.645	3.35	2.97
PA1500RTK-11	1 1/2	1 1/2	1.725	1.850	1.615	1.770	3.70	3.50
PA1500RTK-12	1 1/2	1 1/2	1.850	1.975	1.740	1.895	3.70	3.50
PA1500RTK-13	1 1/2	1 1/2	1.975	2.100	2.020	2.020	3.70	3.50
PA2000RTK-14	2	1 3/4	2.100	2.225	1.990	2.145	4.05	4.15
PA2000RTK-15	2	1 3/4	2.225	2.350	2.115	2.270	4.05	4.15
PA2000RTK-16	2	1 3/4	2.350	2.475	2.240	2.395	4.05	4.15
PA2000RTK-17	2	1 3/4	2.475	2.600	2.365	2.520	4.05	4.15
PA2000RTK-18	2	1 3/4	2.600	2.700	2.490	2.645	4.05	4.15
PA2500RTK-19	2 1/2	1 3/4	2.700	2.850	2.560	2.760	4.10	4.60
PA2500RTK-20	2 1/2	1 3/4	2.850	3.000	2.710	2.910	4.10	4.60
PA3000RTK-21	3	1 3/4	3.000	3.150	2.860	3.060	4.50	5.68
PA3000RTK-22	3	1 3/4	3.150	3.300	3.010	3.210	4.50	5.68
PA3000RTK-23	3	1 3/4	3.300	3.450	3.160	3.360	4.50	5.68
PA3500RTK-24	3 1/2	1 3/4	3.450	3.600	3.300	3.500	4.60	6.02
PA3500RTK-25	3 1/2	1 3/4	3.600	3.750	3.450	3.650	4.60	6.02
PA3500RTK-26	3 1/2	1 3/4	3.750	3.900	3.600	3.800	4.60	6.02
PA4000RTK-27	4	1 3/4	3.900	4.050	3.750	3.940	4.75	6.52
PA4000RTK-28	4	1 3/4	4.050	4.200	3.900	4.090	4.75	6.52
PA4000RTK-29	4	1 3/4	4.200	4.350	4.050	4.240	4.75	6.52

All dimensions are for informational purposes only *Tolerances +/- 5%

