

# PVC COATED MOGUL FITTINGS - BUB

## Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1" to 4"
- Sealing sleeves on all hubs

## Applications:

Calbond PVC Coated Mogul Style Conduit Bodies are used to; act as pull outlets for conductors being installed, provide openings for making splices in conductors, and to provide access to conductors for maintenance and future system changes where an extra larger wiring space is required. They are available in all styles. Sealing mating between cover and fittings are provided.



## Standards:

- UL Standard: 514B
- CSA Standard: C22.2 No. 18

BUB							
Part Number	Trade Size (in)	A (in)	B (in)	C (in)	D (in)	E (in)	Weight per 100 (lbs)
PV1000BUB3	1	10.19	2.73	2.27	1.88	6	3.2
PV1200BUB4	1¼	11.06	3.23	2.27	1.88	6	4.0
PV1500BUB5	1½	15.00	3.54	3.08	2.63	10	5.9
PV2000BUB6	2	15.50	4.17	3.08	2.63	10	7.8
PV2500BUB7	2½	19.75	4.85	4.33	3.81	15	12.5
PV3000BUB8	3	19.88	6.57	4.33	3.81	15	17.0
PV3500BUB9	3½	25.38	6.42	5.33	4.75	20	25.0
PV4000BUB10	4	25.25	6.85	5.33	4.75	20	28.0

